

APPROVAL OF MANUFACTURER CERTIFICATE

Certificate No: AMMM000004M Revision No: 2

This is to certify:

That SIDERFORGEROSSI GROUP S.p.A. Via Mario Schiro, 2 36010 Cogollo del Cengio VI, Italy

is an approved manufacturer of **Steel Forgings**

in accordance with DNV rules for classification – Ships DNV-OS-B101 – Metallic materials

and the following particulars:

Application area	Forgings for hull structures and equipment Forgings for shafting and machinery
	Forgings for gearing
	Forgings for boilers, pressure vessels and piping systems
Steel type	Carbon and carbon-manganese,
	Alloy
Forging method	Open die forging
Max. weight	See page 2
Max. diameter / section	See page 2
Heat treatment condition	See page 2

Manufacturer(s) approved by this certificate is/are accepted to deliver according to DNV GL, DNV and GL rules. Materials to be applied to DNV classed object shall fulfill the material requirements in the applicable DNV class rules.

Issued at Hamburg on 2022-06-24

This Certificate is valid until **2025-06-30**. DNV local station: **Venice**

Approval Engineer: Stefan Röhr

for DNV

Thorsten Lohmann Head of Section

LEGAL DISCLAIMER: Unless otherwise stated in the applicable contract with the holder of this document, or following from mandatory law, the liability of DNV AS, its parent companies and their subsidiaries as well as their officers, directors and employees ("DNV") arising from or in connection with the services rendered for the purpose of the issuance of this document or reliance thereon, whether in contract or in tort (including negligence), shall be limited to direct losses and under any circumstance be limited to 300,000 USD.





Particulars of the approval

Forgings for hull structures and equipment

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	NV F400UW, NV F440UW, NV F480UW, NV F520UW, NV F560UW, NV F600UW	OD	5 000	600	N, NT, QT
Alloy	NV F550AW, NV F600AW, NV F650AW	OD	5 000	600	QT

Forgings for shafting and machinery Forgings for gearing

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
	NV F400U, NV F440U, NV F480U, NV F520U,				
C and C-Mn	NV F560U, NV F600U,	OD	5 000	600	N, NT, QT
	NV F640U, NV F680U, NV F720U, NV F760U				
Alloy	NV F600A, NV F700A, NV F800A, NV F900A,	OD	5 000	600	QT
	NV F1000A, NV F1100A				

Forgings for boilers, pressure vessels and piping systems

Steel type	Grade ³⁾	Forging method ¹⁾	Max. weight [kg]	Max. thickness [mm]	Heat treatment condition ²⁾
C and C-Mn	NV F450H, NV F490H	OD	5 000	600	N, NT, QT
Alloy	NV F0.5Mo, NV F1Cr0.5Mo	OD	5 000	600	N, NT, QT
	NV F2.25Cr1Mo	OD	5 000	600	N, QT

Remarks:

- ¹⁾ OD: Open die forging
- ²⁾ QT: Quenched and tempered; N: Normalized; NT: Normalized and tempered
- ³⁾ Including equivalent grades to other standards